



D-Lite RiCare

Type	• SMD
IP Rating	• 20/50
Operating Voltage	• 90-270 V AC
Color Temperature	• CW/WW/NW
Luminous Efficacy	• >90 lm/W
CRI	• >80
Power Factor	• >0.98
THD	• <10%

- Recess Mounted
- Attractive aesthetics
- Glare free lighting
- Ideal for Hospitals, Laboratories, Offices
- Two springs on opposite sides for easy installation
- CRCA Sheet
- PMMA diffuser for uniform distribution of light
- Separate electronic driver cabin
- Tested as per IS 10322(Part 5/Sec 2):2012

Code	• 201 198 14.24.2
Power Consumption	• 12W
Product Dimensions (axb)	• 169 x 11 mm
Cutout Dia	• 127 mm

Code	• 201 198 14.30.3
Power Consumption	• 15W
Product Dimensions (axb)	• 170 x 23 mm
Cutout Dia	• 140 mm

Code	• 304 143 123.18
Power Consumption	• 18W
Product Dimensions (axb)	• 170 x 23 mm
Cutout Dia	• 140 mm

Code	• 304 143 123.24
Power Consumption	• 24W
Product Dimensions (axb)	• 200 x 25 mm
Cutout Dia	• 175 mm