



D-Lite x-Slim (S)

Type	• LED
IP Rating	• 20/50
Operating Voltage	• 120-240 V AC
Color Temperature	• CW/WW/NW
Luminous Efficacy	• >100 lm/W
CRI	• >80
Power Factor	• >0.95
THD	• <10%

- Ideal for Hospitals, Laboratories, Offices
- Surface Mounted
- Attractive aesthetics
- Glare free lighting
- PMMA diffuser for uniform distribution of light
- CRCA Sheet
- Tested as per IS 10322(Part 5/Sec 2):2012

Code	• 13 02 14.01
Power Consumption	• 8W
Product Dimensions (axb)	• 120x55 mm
Mounting Pitch	• 66 mm
Weight	• 0.31 Kg

Code	• 13 02 14.02
Power Consumption	• 12W
Product Dimensions (axb)	• 170x38 mm
Mounting Pitch	• 166 mm
Weight	• 0.36 Kg

Code	• 13 02 14.03
Power Consumption	• 15W
Product Dimensions (axb)	• 172x38 mm
Mounting Pitch	• 105 mm
Weight	• 0.32 Kg

Code	• 13 02 14.04
Power Consumption	• 24W
Product Dimensions (axb)	• 170x39 mm
Mounting Pitch	• 105 mm
Weight	• 0.37 Kg