



Type	• SMD
IP Rating	• 20/50
Operating Voltage	• 90-270 V AC
Color Temperature	• CW/WW/NW
Luminous Efficacy	• >90 lm/W
CRI	• >80
Power Factor	• >0.98
THD	• <10%

- ideal for corridors, art galleries, retail showrooms and home decor.
- Recess Mounted
- Attractive aesthetics
- The product is fixed/tiltable for light adjustment
- Aluminium Heat Sink
- Tested as per IS 10322 (Part 5/Sec 2):2012

Accessories : (Optional)

- Dimmable Driver
- Honeycomb Louvers

Code	• 206 115 68.06
Power Consumption	• 6W
Product Dimensions (axb)	• 75 x 90/95 x 90 mm
Cutout Dia	• 67 mm / 86 mm

Code	• 206 115 68.12
Power Consumption	• 12W
Product Dimensions (axb)	• 75 x 120/95 x 120 mm
Cutout Dia	• 67 mm / 86 mm

Code	• 206 115 68.18
Power Consumption	• 15W
Product Dimensions (axb)	• 97 x 110 mm
Cutout Dia	• 85 mm

Code	• 206 115 68.24
Power Consumption	• 24W
Product Dimensions (axb)	• 75 x 140/95 x 140 mm
Cutout Dia	• 67 mm / 86 mm